

Digital Seismic Cable

CABLES FOR SN388

- High quality and reliable in low cost
- Application in 2-D & 3-D seismic exploration
- Suitable for land, transition zone, marsh



DT-Digital Seismic Cable for SN388

Item	SC14T/2P	FSC14T/2P	FSC10T/2P	SC9T/4P
Type of field	Dry	Dive	Dive	Dry
Water blocking material	No	Yes	Yes	No
Maximal operational depth in water	Rainy	10m	10m	Rainy
Outside diameter	10mm	10.5mm	8.2mm	10.5mm
Minimum jacket thickness	1.1mm	1.2mm	1mm	1.1mm
Jacket material	TPU	TPU	TPU	TPU
Kevlar	Yes	Yes	Yes	No
Operating temperature range	-40°C+70°C	-40°C~+70°C	-40°C ~+70°C	-40°C~+70°C
Storage temperature range	-55°C+85°C	-55°C +85°C	-55°C ~+85°C	-55°C~+85°C
Number of flexing	>=20000	>=20000	>=10000	>=15000
Weight	103kg/km	112kg/km	70kg/km	90kg/km
Pull	1100N	1100N	12005	800N

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.