

# DTCC LEADER WIRES (DLW)



D-loop options: Molded, Clip-on Poly D-loop or metal D-loop at specified intervals.

Type Number	O.D.		BreakStrength		Weight		Ohms	
	In.	mm	lbs.	Kg	Lb/Mft.	Kg/km	Mft.	Km
DLW-2-70-180	0.180	4.6	140	63.5	16.0	23.8	35.1	115
DLW-2-70-180 F	0.180	4.6	140	63.5	15.7	23.4	35.1	115
DLW-3-70-180	0.180	4.6	210	95.3	17.7	26.3	35.1	115
DLW-3-70-180 F	0.180	4.6	210	95.3	17.5	26.0	35.1	115
DLW-2-70-210	0.210	5.3	140	63.5	20.0	29.8	35.1	115
DLW-2-70-210 F	0.210	5.3	140	63.5	19.8	29.5	35.1	115
DLW-3-70-210	0.210	5.3	210	95.3	21.8	32.4	35.1	115
DLW-3-70-210 F	0.210	5.3	210	95.3	21.6	32.1	35.1	115
DLW-2-70-250	0.250	6.4	140	63.5	27.7	41.2	35.1	115
DLW-2-70-250 F	0.250	6.4	140	63.5	27.4	40.8	35.1	115
DLW-3-70-250	0.250	6.4	210	95.3	29.4	43.7	35.1	115
DLW-3-70-250 F	0.250	6.4	210	95.3	29.2	43.4	35.1	115
DLW-2-100-180	0.180	4.6	200	90.7	18.1	26.9	35.1	79
DLW-2-100-180 F	0.180	4.6	200	90.7	17.7	26.4	35.1	79
DLW-2-100-210	0.210	5.3	200	90.7	22.2	33.0	35.1	79
DLW-2-100-210 F	0.210	5.3	200	90.7	21.8	32.5	35.1	79
DLW-3-100-210	0.210	5.3	300	136.1	25.0	37.2	35.1	79
DLW-3-100-210 F	0.210	5.3	300	136.1	24.7	36.7	35.1	79
DLW-2-100-225	0.225	5.7	200	90.7	24.8	36.9	35.1	79
DLW-2-100-225 F	0.225	5.7	200	90.7	24.4	36.3	35.1	79
DLW-3-100-225	0.225	5.7	300	136.1	27.6	41.1	35.1	79
DLW-3-100-225 F	0.225	5.7	300	136.1	27.3	40.6	35.1	79
DLW-2-100-250	0.250	6.4	200	90.7	29.8	44.3	35.1	79
DLW-2-100-250 F	0.250	6.4	200	90.7	29.4	43.8	35.1	79
DLW-3-100-250	0.250	6.4	300	136.1	32.6	48.5	35.1	79
DLW-3-100-250 F	0.250	6.4	300	136.1	32.3	48.0	35.1	79
DLW-2-100-310	0.310	7.8	200	90.7	41.5	61.8	35.1	79
DLW-2-100-310 F	0.310	7.8	200	90.7	41.2	61.3	35.1	79
DLW-3-100-310	0.310	7.8	300	136.1	44.4	66.0	35.1	79
DLW-3-100-310 F	0.310	7.8	300	136.1	44.0	65.5	35.1	79
DLW-2-225-310	0.310	7.87	450	204.1	59.3	80.80	4	29

DLW - 2 - 70 - 180 - F  
 1      2      3      4      5

1. Manufacturer brand

2. Number of conductors

Typical number of conductor: 2, 3,

3. Break strength per conductor lbs

Typical break strength of each conductor:  
 70lbs, 100lbs, 225lbs.

4. Wire O.D

Wire outside diameter in inches (Typically)  
 I.E 0.180", 0.210", 0.250", 0.310".

5. Indicates jel filled

"F" Indicates the Wire is filled with water  
 blocking jel